



STOCK SHEET

916.386.2233

Send orders to orders@repcor1.com

No Minimum Order

Freight Terms: FFA \$2,500 Net

Effective September 2022



ORIGINS ACTIVSENSE FAUCET

LIST PRICE



SYM-S6960B

Origins lavatory sensor faucet w/ touchless ActivSense technology

Chrome Finish

\$533.15

MAXLINE THERMOSTATIC VALVES



SYM-7-225-CK-F

Maxline TMV 1/2" female NPT connection

\$237.00

SYM-7-225-CK-MS

Maxline TMV 1/2" male sweat connection

\$237.00



SYM-7-230-CK-FS

Maxline TMV 3/4" female sweat connection

\$268.55

SYM-7-230-CK-M

Maxline TMV 3/4" male NPT connection

\$268.55



SYM-8210CK

Maxline Tempering Valve

\$117.70



SYM-7-102

Tempcontrol-photo process unit

\$1,181.60

SYM-7-200

Tempcontrol valve

\$1,210.25



SYM-7-400

Tempcontrol Valve

\$1,595.70

SYM-7-500

Tempcontrol Valve

\$1,875.40

SYM-7-700

Tempcontrol Valve

\$1,909.65

SYM-7-900

Tempcontrol Valve

\$2,182.00



SYM-7-1000

Tempcontrol Assembly

\$2,717.60

Table 1: Flow Rate - gpm (L/min)								
Valve Model	Min. Flow Rate*	Min. Flow Rate (per ASSE 1017)	Pressure Differential - psi (kPa)					
			5 psi (34 kPa)	10 psi (69 kPa)	20 psi (138 kPa)	25 psi (172 kPa)	30 psi (207 kPa)	45 psi (310 kPa)
7-102	0.5 gpm (1.9 L/min)	0.5 gpm (1.9 L/min)	1 gpm (4 L/min)	3 gpm (11 L/min)	6 gpm (23 L/min)	7 gpm (27 L/min)	8 gpm (30 L/min)	11 gpm (42 L/min)
7-200	0.5 gpm (1.9 L/min)	5 gpm (19 L/min)	7 gpm (27 L/min)	12 gpm (46 L/min)	18 gpm (68 L/min)	21 gpm (80 L/min)	23 gpm (87 L/min)	27 gpm (102 L/min)
7-400	0.5 gpm (1.9 L/min)	9 gpm (34 L/min)	18 gpm (68 L/min)	27 gpm (102 L/min)	37 gpm (140 L/min)	41 gpm (155 L/min)	44 gpm (167 L/min)	53 gpm (201 L/min)
7-500	0.5 gpm (1.9 L/min)	13 gpm (49 L/min)	22 gpm (83 L/min)	38 gpm (144 L/min)	50 gpm (190 L/min)	55 gpm (209 L/min)	59 gpm (224 L/min)	70 gpm (265 L/min)
7-700	0.5 gpm (1.9 L/min)	13 gpm (49 L/min)	25 gpm (95 L/min)	43 gpm (163 L/min)	57 gpm (216 L/min)	62 gpm (235 L/min)	66 gpm (250 L/min)	77 gpm (292 L/min)
7-900	0.5 gpm (1.9 L/min)	13 gpm (49 L/min)	30 gpm (114 L/min)	55 gpm (209 L/min)	76 gpm (288 L/min)	84 gpm (318 L/min)	89 gpm (337 L/min)	104 gpm (394 L/min)
7-1000	0.5 gpm (1.9 L/min)	13 gpm (49 L/min)	38 gpm (144 L/min)	67 gpm (254 L/min)	100 gpm (379 L/min)	111 gpm (421 L/min)	120 gpm (455 L/min)	140 gpm (531 L/min)

TempControl Valve Sizes		
Model No.	Inlet	Outlet
7-900	1-1/2"	1-1/2"
7-1000	1-1/2"	2"

TempControl Valve Sizes		
Model No.	Inlet	Outlet
7-200	3/4"	3/4"
7-400	3/4"	1"
7-500	1"	1-1/4"
7-700	1-1/4"	1-1/2"

*Minimum flow rate when valve is installed at or near the hot water source with recirculated tempered water and continuously operating circulating pump.